

GTC-154

4.0 Megapixel FULL HD Network IP Dome Camera



KEY FEATURES

- *1/3" Progressive Sony CMOS
- *H.264 / MPEG4 / MJPEG video compression
- *4.0 Megapixel
- *Full HD 2592*1520
- *Smart IR Mode, 36pcs IR LED
- *IR LED Module (Distance up to 35m)
- *Vandal proof Housing
- *Digital WDR
- *Slow Shuttle
- *Privacy Masks
- *Day/Night (ICR)
- *3D Noise Reduction
- *Support Audio*Optional
- *ONVIF supported

TECHNICAL SPECIFICATIONS



Model No.	GTC-154
Image sensor	1/3" Progressive Sony CMOS
Min. Illumination	0.01 lux (Color); 0.001 lux (B&W)
Shutter Time	1/25s or 1/30s ~ 1/67500s
Lens	3.6 / 6 / 8mm @ F1.2
Video compression	H.264 & MJPEG dual-stream encoding
Frame rate	4MP(2592x1520)/3M(2048x1536)/1080P(1920x1080)/720P(1280x720)/D1(704x576)/CIF(352x288)
Image settings	Saturation, brightness, contrast adjustable through client software or web browser
2D Wide Dynamic Range (WDR)	Off / on
3D Noise Reduction	Off / 1 – 32 selectable
Privacy Masking	Off / on (4 zones)
Operating conditions	-10° ~ 60°C (14°F - 140°F) Humidity 90% or less (non-condensing)
Power supply	DC12V / POE
IR range	35 Meters
Network Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP (SNMP, HTTPS, SIP, FTP, SRTP, 802.1x, Ipv6 optional)
Mobile Phone	iPhone, iPad, and Android support
Local storage <i>*Optional</i>	Micro SD/SDHC slot, up to 32GB
Audio input & output <i>*Optional</i>	1-ch microphone input
Alarm input & output <i>*Optional</i>	2
Alarm trigger <i>*Optional</i>	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Dimensions	120mm x 85mm
Weight	500g

**Design and specifications are subject to change without prior notice.*