

GTC-FA116 Face Recognition Attendance System



PRODUCT DESCRIPTION

GTC-FA116 is the latest in control technology a full touch 3-inch color screen facial machine, set attendance and access control in one supports a variety of authentication methods (face, card, card + face, password, face + password, password + card, face + card + password), in the control the latest technology ZEM810 core board, ZK Face latest face recognition algorithm, large capacity, fast identification, integrated high-resolution night vision infrared and color camera function, the scope wide, not subject to the influence of external light, whether it is or in the dark under the glare can be performed effectively identify. Authentication system, applicable in many fields and enterprises attendance and access control management.

FEATURES

- *High-resolution infrared and color cameras
- *Full-color touch screen, easy to operate, simple and stylish interface
- *The infrared optical system, ability to use the environment, outdoor (non-direct sunlight), the nighttime can still identify
- *Beard, glasses, bangs covering natural expression, exaggerated facial expressions may identify
- *Standard TCP / IP, support for inter-network inter-gateway connection
- *The slim, ergonomic design, significantly improve recognition Comfort
- *Access control function, power locks, exit switch, alarm, door sensor, a variety of authentication methods.

SPECIFICATIONS

Model No	GTC-FA116
Card Capacity	10000
Facial capacity	200
Recording capacity	100000 inch high-definition color touch screen
Facial recognition algorithm	ZK Face the latest high-speed face recognition algorithm
Camera	High-resolution infrared and color camera
Means of communication	TCP / IP network communications U disk function
Swipe function	ID card
Attendance function	T9 input method, 9 yards, recorded query, the timing of state transitions, horn rings
Access control function	Power locks, exit switch, alarm, door sensor, multiple authentication methods
Optional functions	Mifare card
The use of humidity	0°C-45 °C
Operating Temperature	20% -80%
Power Specifications	DC 12V
Language Selection	English
Product Size	105mm x 160mm x36mm

Design and specifications are subject to change without notice.